

Ι\_

# PL1S -SIMMA / RIVALIT LUFT

## Air/Water - 20 bar

#### **Application:**

\_ |

A flexible air and water hose for use in industry, commerce and on construction sites.

## Temperature range:

-30°C / +80°C.

## Safety factor:

3:1

## Tube:

Synthetic rubber, black, suitable for oil-laden air, antistatic, smooth.

### **Reinforcement:**

Textile spiral.

#### Cover:

Synthetic rubber, black, resistant to ozone and weather, antistatic, smooth.

### Marking:

continuous inkjet, white letters: RIVALIT Druckluft/Wasser Air/Water Hose Working pressure 300 PSI - Burst pressure 900 PSI ID" Made in Europe



Article number	Internal-Ø in		Wall width	External-Ø	Work. pressure	Number of inserts	Bending radius	Weight approx.	Coil length
	mm	inch	in mm	in mm	(max.) bar		(min.) in mm	kg/m	(max.) m
68440 1336	13,0	1/2	3,5	20,0	20	2	75	0,28	100
68440 1946	19,0	3/4	4,5	28,0	20	2	120	0,51	100
68440 2558	25,0	1	5,0	35,0	20	2	150	0,73	100

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. In order to always have the latest product and safety information make sure you visit our website (www.semperflex.com) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts with Semperflex are exclusively aut general information about the range, choice and safe use of our products can be found at our website (www.semperflex.com) and must be followed without exception. Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the latest state-of-the-art industrial technology and many years of experience and testing: whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620:2005(E). However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the cast logue or individual databets are therefore stirctly subject to the continuous observance of all specifications reparting resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance or handling (e.g. squashing, rupturing, stretching or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Unless specified otherwise, all hoses are manufactured according to ENISO 1307:2008.



ı\_\_\_\_

1